



# STAINLESS PLUS

## LIQUID STAINLESS PRESOAK

### PRODUCT USES

Liquid pre-soak formulated to remove tough food soils on stainless flatware and aluminum pots and pans.

### OPERATOR BENEFITS

- Easily and effectively soaks food soils from stainless steel.
- Brightens tableware.
- Excellent for soaking off heavy, baked on food soils from aluminum pots and pans.

### DIRECTIONS FOR USE

#### For pre-soaking stainless steel:

1. Dilute 1 to 2 oz. of product per 1 gallon of hot water in a pre-soak pan or sink.
2. Place flatware in pre-soak tank as soon as possible after use.
3. Soak stainless steel flatware in the solution for at least 5 minutes.
4. Rinse with clean water before washing.
5. **DO NOT SOAK** longer than 30 minutes.
6. **DO NOT USE** on sterling silver or silver plated flatware.
7. **DO NOT USE** on ware with wooden handles.

#### For pre-soaking aluminum pots and pans:

To remove medium buildup - Dilute 2 to 4 oz. per gallon for soaking.  
To remove heavy buildup - Dilute 6 oz. per gallon for soaking.

### PRODUCT SPECS

<b>Pack sizes:</b>	4/1 Gal.	<b>Color:</b>	Slight yellowish
<b>Characteristics:</b>	Non-viscous liquid	<b>Odor:</b>	Characteristic
<b>Rinsability:</b>	Excellent	<b>Foam:</b>	Moderate
<b>Flammability:</b>	NA	<b>pH in 1% solution:</b>	11.5 - 11.7
<b>Biodegradable:</b>	Yes	<b>Phosphorous content:</b>	0.0%

### IMPORTANT OPERATOR INFORMATION

#### MSDS:

Refer to the Material Safety Data Sheet (MSDS) supplied by your distributor for information on emergency response, safe usage, hazards, first aid and proper product handling.

#### Emergency Response Phone:

1-800-424-9300

#### Statement of

#### Practical Treatment:

If swallowed: Dilute by giving large amounts of water and call a physician.  
For eye or skin contact: Flush with cool water for 15 minutes and call a physician.

#### Product Precautions:

#### **DANGER: CORROSIVE**

Harmful if swallowed. Irritating to eyes and skin.

#### **KEEP OUT OF REACH OF CHILDREN.**

#### Shipping Classification:

UN 1760, Corrosive Liquid, N.O.S., Class 8, PG II  
(Contains Sodium Hypochlorite, Potassium Hydroxide)  
**CORROSIVE**