



CARBON REMOVER/ SMOKER CLEANER

PRODUCT USES	Removes heavy, baked on grease, oils, pitch build-up and carbonized soils.	
OPERATOR BENEFITS	<ul style="list-style-type: none"> • Refurbishes greasy, smokehouse surfaces. • Cleans and removes heavy carbonized soils. 	
DIRECTIONS FOR USE	<ol style="list-style-type: none"> 1. Mixing instructions: <ul style="list-style-type: none"> • Mix ½ - 2 Oz. per gallon for foaming device application. • Mix 1 - 5 Oz. per gallon for spray bottle application. • Increase solution strength for heavier soils. 2. Apply Carbon Remover through a hose-end foamer. <ul style="list-style-type: none"> • For smaller areas apply with a trigger spray bottle. 3. Allow cleaning solution to the penetrate soils completely. 4. Rinse thoroughly. 5. Properly sanitize food contact surfaces with a Quaternary Sanitizer. Wear Gloves and Eye Protection When Using CARBON REMOVER.	
PRODUCT SPECS	Pack size: 4/1 Gal. Characteristics: Non-viscous liquid Rinsability: Excellent Flammability: NA	Color: Light amber Odor: Characteristic Foam: Copious pH in conc. form: 12.3 – 12.8 Phosphorous content: 0.0%
IMPORTANT OPERATOR INFORMATION		
SDS:	Refer to the Safety Data Sheet (SDS) supplied by your distributor for information on emergency response, safe usage, hazards, first aid and proper product handling.	
Emergency Response Phone:	1-800-424-9300	
Statement of Practical Treatment:	If swallowed: Dilute by giving large amounts of water and call a physician. For eye or skin contact: Flush with cool water for 15 minutes and call a physician.	
Product Precautions:	DANGER: CORROSIVE Harmful if swallowed. Injurious to eyes and skin. KEEP OUT OF REACH OF CHILDREN.	
Shipping Classification:	UN 1760, Corrosive Liquid, N.O.S., Class 8, PG II (Contains Potassium Hydroxide) CORROSIVE	