



# LIQUID FLATWARE PRESOAK

## PRODUCT USES

An economical presoak that removes tough food soils from stainless flatware and loosens baked-on food soils for easier washing.

## OPERATOR BENEFITS

- Economical flatware presoak.
- Removes tough food soils on stainless flatware.
- Effectively loosens baked-on food soils for easier washing.

## DIRECTIONS FOR USE

### For Pre-soaking Stainless Steel Flatware:

1. Dilute 2 to 3 oz. of product per 1 Gallon of hot water in a pre-soak pan or sink.
2. Place flatware in pre-soak tank as soon as possible after use.
3. Soak stainless steel flatware in the solution for at least 5 minutes.
4. Rinse with clean water before washing.

**DO NOT SOAK LONGER THAN 30 MINUTES.**

**DO NOT USE ON STERLING SILVER OR SILVER PLATED FLATWARE.**

**DO NOT USE ON WARE WITH WOODEN HANDLES.**

### For Pre-soaking Aluminum Pots and Pans:

- To remove medium buildup – Dilute 3 to 5 oz. per Gallon for soaking.
- To remove heavy buildup – Dilute 8 oz. per Gallon for soaking.

## PRODUCT SPECS

<b>Pack sizes:</b>	4/1 Gal., 5 Gal.	<b>Color:</b>	Clear blue
<b>Characteristics:</b>	Non-viscous liquid	<b>Odor:</b>	Characteristic
<b>Rinsability:</b>	Excellent	<b>Foam:</b>	Very limited
<b>Flammability:</b>	NA	<b>pH in conc. form:</b>	12.0 – 13.0
		<b>Phosphorous content:</b>	0.0%

## IMPORTANT OPERATOR INFORMATION

### MSDS:

Refer to the Material Safety Data Sheet (MSDS) supplied by your distributor for information on emergency response, safe usage, hazards, first aid and proper product handling.

### Emergency Response Phone:

1-800-424-9300

### Statement of

### Practical Treatment:

If swallowed: Dilute by giving large amounts of water and call a physician.

For eye or skin contact: Flush with cool water for 15 minutes and call a physician.

### Product Precautions:

CAUTION. Harmful if swallowed. Injurious to eyes and skin.

**DANGER: KEEP OUT OF REACH OF CHILDREN.**

### Shipping Classification:

Compound, cleaning. Liquid, CLASS 8, NA 1760, PG III  
(Contains Potassium Hydroxide)

**CORROSIVE**