



FLATWARE PRESOAK POWDER - ERP

PRODUCT USES

An Environmentally Safe powdered flatware pre-soak. Removes tough food soils on stainless flatware. Effectively loosens baked-on food soils for easier washing.

OPERATOR BENEFITS

- Environmentally friendly product (ERP).
 - Non-corrosive, phosphate free, does not contain hazardous solvents.
 - Easily soaks food soils from stainless steel and stainless flatware.
 - Brightens flatware ware.
 - 10 lb tubs offers E-Z open, moisture-free storage.

DIRECTIONS FOR USE

For Pre-soaking Stainless Steel:

1. Dilute 1 oz. of product per 1 Gallon of hot water in a pre-soak pan or sink.
2. Place flatware in pre-soak tank as soon as possible after use.
3. Soak stainless steel flatware in the solution for at least 5 minutes.
4. Rinse with clean water before washing.
5. Do not soak longer than 30 minutes.
6. Do not use on sterling silver or silver plated flatware.
7. Do not use on ware with wooden handles.

For Pre-soaking Aluminum Pots and Pans:

To remove medium buildup – Dilute 2 to 3 oz. per Gallon for soaking.
 To remove heavy buildup – Dilute 6 oz. per Gallon for soaking.

PRODUCT SPECS

Pack sizes:	2/10 lb. tubs	Color:	White
Characteristics:	Free-flowing powder	Odor:	None
Rinsability:	Excellent	Foam:	Moderate
Flammability:	NA	pH (Undiluted):	11.0 – 11.8
Biodegradable:	Yes	Phosphorous content:	0.0%

IMPORTANT OPERATOR INFORMATION

MSDS:

Refer to Material Safety Data Sheet (MSDS) supplied by your distributor for information on emergency response, safe usage, hazards, first aid, and proper product handling.

Emergency Response Phone:

1-800-424-9300

Statement of

Practical Treatment:

If swallowed: Dilute by giving large amounts of water or milk and call a physician.
 For eye or skin contact: Flush with cool water for 15 minutes and call a physician.

Product Precautions:

DANGER: OXIDIZING SOLID

Harmful if swallowed. Irritating to eyes and skin.

KEEP OUT OF REACH OF CHILDREN

Shipping Classification:

UN 1479, Oxidizing Solid, CLASS 5.1, N.O.S., PG III
 (Contains Sodium Percarbonate & Sodium Metasilicate Anhydrous)
OXIDIZING SOLID

809 ER 1/3/18

The information contained herein has been compiled from sources considered accurate and reliable. Since actual use conditions are beyond TMA's control, no warranty, expressed or implied, is made.

TECHNICAL MARKETING ALLIANCE / Chemnet Systems

www.chemnet-systems.com