TMA /Chemnet
ALIGNING THE INTERESTS OF DISTRIBUTORS AND OPERATORS - SINCE 1996

PRO-DRY XL

Concentrated
All Temperature Rinse Aid

PRODUCT USES	An economical liquid, concentrated rinse aid for use in high temperature or low temperature dishmachines. Provides fast drying and prevents film or spots on tableware. It is extremely effective on plasticware.
OPERATOR BENEFITS	• Environmentally Safe. • Contains no Alkylphenol surfactants. • Fast-drying. • Eliminates film and spots on tableware and plasticware.
DIRECTIONS FOR USE	1. Carefully open the container to prevent spilling or splashing. 2. Insert the rinse aid pickup tube into the container opening. 3. The rinse aid is then dispensed automatically into the dishmachine. 4. Replace with new container when empty. 5. Rinse empty thoroughly with water and discard, Contact Your Chemical Specialist To Calibrate Your Rinse Aid Dispenser
PRODUCT SPECS	Pack sizes: 5 Gal. Characteristics: Non-viscous liquid Rinsability: Excellent Flammability: NA Phosphorous content: 0.0% Color: Clear blue Odor: Nil Foam: Very limited pH in conc. form: 6.0 - 8.0

IMPORTANT OPERATOR INFORMATION

MSDS:	Refer to the Material Safety Data Sheet (MSDS) supplied by your distributor for information on emergency response, safe usage, hazards, first aid and proper product handling.
Emergency Response Phone:	1-800-424-9300
Statement of Practical Treatment:	**If swallowed:** Dilute by giving large amounts of water and call a physician. **For eye or skin contact:** Flush with cool water for 15 minutes and call a physician.
Product Precautions:	CAUTION. Harmful if swallowed. Injurious to eyes and skin. DANGER: KEEP OUT OF REACH OF CHILDREN.
Shipping Classification:	Not Regulated

INGREDIENTS: Water CAS# 7732-18-5, Diluent; Methyl oxirane copolymer with oxirane CAS# 9003-11-6, Cleaning agent; Sodium xylene sulfonate CAS# 1300-72-7 Hydrotrope; Sulfonated hydrotrope withheld as CBI; FD&C Blue #1 CAS# 3844-45-9, Colorant.

The information contained herein has been compiled from sources considered accurate and reliable. Since actual use conditions are beyond TMA's control, no warranty, expressed or implied, is made.