

TileWorx





PRODUCT USES	Excellent for cleaning quarry tile floors, tile walls, and stainless steel kitchen equipment.	
OPERATOR BENEFITS	 Economical use cost due to highly concentrated formula. Alkaline based formula cuts grease and reduces slipperiness of tile floors. Bleach-fortified formula cleans and brightens grout. May also be used to clean kitchen wall tiles. Refillable spray bottle lets you spot-clean stubborn soils. 	
DIRECTIONS FOR USE	 Wear rubber gloves and goggles when using this product. Floor cleaning: Dilute this product at a ratio of 1 to 32 and repeat if necessary. Use hot water, fill a floor mop bucket, apply directly to the floor, and wait 2 minutes for solution to penetrate soils. Rinse mop, wring out, and mop up any excess liquid. Repeat if necessary. Hard surface cleaning: Dilute this product at a ratio of 1 to 64 when using a hydraulic proportioning dispenser. Spray product directly on the area to be cleaned. Wipe surface with a clean, wet sponge or cloth. Rinse sponge or cloth in clean water, wring out, and then wipe up any excess cleaning solution. Repeat if necessary. 	
EQUIPMENT NEEDED	Rubber gloves, chemical goggles, a hydraulic proportioning dispenser, mop, mop bucket, sponge, cleaning cloth, and a properly identified TMA spray bottle.	
PRODUCT SPECS	Pack size: 4/.5 GAL Characteristics: Non-viscous liquid Rinsability: Excellent	Color: Slight straw color Odor: Slight chlorine Foam: Moderate

IMPORTANT OPERATOR INFORMATION

SDS: Refer to the Safety Data Sheet (SDS) supplied by your distributor for information on

emergency response, safe usage, hazards, first aid and proper product handling.

pH in conc. form: Very alkaline

Phosphorous content: 0.0%

Emergency Response Phone: 1-800-424-9300

Statement of

If swallowed: Dilute by giving large amounts of water or milk and call a physician. **Practical Treatment:** For eye or skin contact: Flush with cool water for 25 minutes and call a physician.

DANGER: CORROSIVE **Product Precautions:**

Harmful if swallowed. Irritating to eyes and skin.

KEEP OUT OF REACH OF CHILDREN.

Shipping Classification: UN1760, Corrosive Liquid, N.O.S., Class 8, PG II

Flammability: NA

Biodegradable: Yes

(Contains Sodium Hypochlorite, Potassium Hydroxide)

CORROSIVE

INGREDIENTS: Water (7732-18-5); Sodium hypochlorite (7681-52-9); Potassium hydroxide (1310-58-3); Benzenesulfonic

acid, decyl(sulfophenoxy)-, disodium salt (36445-71-3); Sulfonic acids, C10-18-alkane, sodium salts (68608-26-4); Lauramine oxide (1643-20-0); Tetrasodium ethylenediamine tetraacetate (64-02-8); Benzenesulfonic acid, oxybis[decyl-, disodium salt (70146-13-3); Sodium sulfate (7757-82-6)

www.chemnet-systems.com